



DATA SHEET





Impermeability special Manometer for gas network



Easy to use



Selection of units



Hold-min-max functions



Adjustable blacklight

Features

- Pressure measurement
- Selection of units
- Manual self-calibration
- Display of minimum and maximum values
- Configurable auto shut-off

Technical specifications

-0-

OK

MP 130

Parameter	Accuracy*	Measuring range	Resolution
Pressure	From -20 to 20 mbar: $\pm 0.4\%$ of reading ± 0.3 mbar From -500 to -20 mbar and from 20 to 500 mbar: $\pm 0.1\%$ of reading ± 0.6 mbar	From -500 to +500 mbar	From -20 to 20 mbar: 0.01 mbar From -500 to -20 mbar and from 20 to 500 mbar: 0.1 mbar


General features

Measuring units	kPa, inWg, mbar, mmHg, daPa		
Measuring range	Piezoresistive sensor		
Tolerated overpressure	700 mbar		
Connector	\emptyset 4.6 mm threaded connectors made of nickeled brass		
Display	4 lines, LCD technology. Dimensions 50 x 36 mm. 2 lines of 5 digits with 7 segments (value) 2 lines of 5 digits with 16 segments (unit)		
Housing	ABS, protection IP54		
Keypad	5 keys		
European directives	2014/30/EU EMC; 2014/35/EU Low Voltage; 2011/65/EU RoHS II; 2012/19/EU WEEE		
Power supply	4 batteries AAA LR03 1.5 V		
Battery life	180 hours		
Ambience	Neutral gas		
Conditions of use (°C, %RH, m)	From 0 to +50 °C. In non condensing conditions. From 0 to 2000 m.		
Storage temperature	From -20 to +80 °C		
Auto shut-off	Adjustable from 0 to 120 min		
Weight	220 g		


Operating principle

Piezoresistive sensor The pressure deforms the silicon layer. This layer deformation generates a voltage at its terminates.

This voltage is proportional to the pressure applied.



Dimensions (in mm)



Kit content

Designation	reference	Description
MP 130	24619	Impermeability special Manometer for gas network with seal kit, magnetic protective housing, adjustment certificate and transport case

Certificate

Adjustment certificate: An adjustment certificate is a document that ensures the conformity of the device with the tolerances of the data sheet. It ensures that the device has followed the manufacturing process.

Maintenance

We carry out calibration, adjustment and maintenance of your instruments to guarantee a constant level of quality of your measurements. As part of Quality Assurance Standards, we recommend you to carry out a yearly checking.

Seal kit includes

Connectors





Stainless steel female connector, 9 mm diameter



Plug: outside diameter: 22-44 mm 9 mm male connector



Tap with 2 valves and 3 channels

Pressurization pump

Connections

Plugs



6-20

M20 x 1.5

1/2G

Fast connector







10-32



Male bottle



Uw distributeur Hitma B.V.

Vragen over handmeters: www.hitma-handmeters.nl tel.: +31 (0)36 535 06 51

